OT-mini 6

Micro Centrifuge

The OT-mini 6 centrifuge is a simple minifuge for quick spin-downs by closing the centrifue lid



Features

· Supplied with rotors A2.0-6 & A0.2-16

· Electro sensitive non-contacting lid sensor

· Safety stop by opening the lid

Technical Specifications

	OT-mini 6
Max. RPM	6,500 rpm
Max. RCF	2,234 xg (1.5/2.0 mL tube) 1,412 xg (PCR strip)
Max. capacity	6 x 1.5/2.0 ml 2 PCR strips
Speed accuracy	±10%
Time control	Selectable, Short (12 sec) or Continuous (15 min)
Noise level (dependent on rotor)	≤56 dB
Safety lid lock	Yes
Power supply (V/Hz)	100-230V, 50/60Hz
Power Requirement (VA)	7W
Dimension (W x D x H, mm)	150 x 150 x 103
Weight without rotor	650 g
Cat. No.	OT-mini 6

OPTIKA Srl - info@optika-italy.com

OPTIKA reserves the right to make corrections, modifications, enhancements, improvements and other changes to its products at any time without notice.

Fixed Angle Rotor

A2.0-6



- Capacity : 6 x1.5/2.0 mL
- Max. RPM : 6,500
- Max. RCF : 1,710 xg
- Supplied with centrifuge

Adaptors

Tube type (mL)	Max. RCF (xg)	Adaptor Cat. No.
0.5	1,710	TR0.5(2)
0.2	1,379	TR0.2(2)

PCR Rotor

A0.2-16



- Capacity : 16 x 0.2 mL
- Max. RPM : 6,500
- Max. RCF : 1,412 xg
- Supplied with centrifuge



OPTIKA Srl - info@optika-italy.com

OPTIKA reserves the right to make corrections, modifications, enhancements, improvements and other changes to its products at any time without notice.